SAMSUNGClimate Solutions





Floor Console

Floor Console

- Slim design: only 199 mm in depth.
- Two separate air outlets to avoid stratification.
- Long-life washable permanent filter.

- Can be controlled by Smartphone via Wi-Fi Kit (Optional).
- Wireless remote controller (AR-EH03E) included as standard.







Specifications







Model		Outdoor Indoor	AC026RXADKG/EU AC026RNJDKG/EU	ACO35RXADKG/EU ACO35RNJDKG/EU	AC052RXADKG/EU AC052RNJDKG/EU			
Electrical								
Power Supply	Outdoor	Ф, #, V, Hz	1Ф, 2, 220-240 V, 50 Hz	1Ф, 2, 220-240 V, 50 Hz	1Ф, 2, 220-240 V, 50 Hz			
	Indoor	Ф, #, V, Hz	1Ф, 2, 220-240 V, 50 Hz	1Ф, 2, 220-240 V, 50 Hz	1Ф, 2, 220-240 V, 50 Hz			
MCA	System (Outdoor/Indoor)	A	11.0 (10.0 / 1.0)	11.0 (10.0 / 1.0)	17.5 (16.5 / 1.0)			
MFA	System	A	12.5	12.5	20.6			
Minimum SSC value	Outdoor	MVA	Not Applicable	Not Applicable	Not Applicable			
Interconnecting Communication Cable		mm²	Screened 0.75-1.5mm², 2 Core, F1 F2 Connection					
Performance ¹								
Nominal Cooling Capacity	Total Cooling (Sensible Cooling)	kW	2.6 (2.2)	3.5 (2.7)	5.0 (3.4)			
UK Cooling Capacity	Total Cooling (Sensible Cooling)	kW	2.4 (2.1)	3.3 (2.6)	4.8 (3.3)			
Nominal Heating Capacity		kW	3.5	4.0	5.6			
Operating Temperature Range	Cooling	°C	-15.0 ~ 46.0 °C	-15.0 ~ 46.0 °C	-15.0 ~ 50.0 °C			
	Heating	°C	-20.0 ~ 24.0 °C	-20.0 ~ 24.0 °C	-20.0 ~ 24.0 °C			
Energy Efficiency ²								
Rated Efficiency	EER (Nominal Cooling)	W/W	3.61	3.12	2.79			
	COP (Nominal Heating)	W/W	3.30	3.07	3.01			
Seasonal Efficiency	SEER / Energy Label	W/W	6.4/ A++	6.1 / A++	5.9 / A+			
	SCOP / Energy Label	W/W	4.2 / A+	4.1 / A+	4.0 / A+			
Air Flow Rate								
Indoor Unit Airflow Rate	H/M/L	l/s	125 / 113 / 100	142 / 120 / 103	157 / 140 / 123			
Outdoor Unit Airflow Rate		l/s	500	500	667			
Piping Connections								
Liquid Pipe		ø, mm (inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)			
Gas Pipe		ø, mm (inch)	9.52 (3/8)	9.52 (3/8)	12.7 (1/2)			
Drain Pipe		ø, mm	ID 18mm Hose	ID 18mm Hose	ID 18mm Hose			
Max Piping Length (Height)		m	20 (15)	20 (15)	30 (20)			
Refrigerant								
Туре				R32 (Fluorinated greenhouse gas, GWP=675)				
Factory Charging		kg	0.9	0.9	1.2			
		tCO₂e	0.61	0.61	0.81			
Precharge to		m	20	20	10			
Additional Charge		g/m	-	-	15			
Sound								
Indoor Sound Pressure Level	H/M/L	dB(A)	36 / 31 / 26	38 / 34 / 30	43 / 39 / 35			
Indoor Sound Power Level		dB(A)	53	55	60			
Outdoor Sound Pressure Level	Cooling / Heating	dB(A)	46 / 47	48 / 48	48 / 48			
Outdoor Sound Power Level		dB(A)	59	61	62			
Dimensions								
Net Weight	Indoor Unit/Outdoor Unit	kg	16.0 / 32.5	16.0 / 32.5	16.0 / 43			
Indoor Unit Net Dimensions	WxHxD	mm	720 x 620 x 199	720 x 620 x 199	720 x 620 x 199			
Outdoor Unit Net Dimensions	WxHxD	mm	790 x 548 x 285	790 x 548 x 285	880 x 638 x 310			

Accessories							
Wireless Remote Controller	Touch Wired Controller	Premium Wired Controller	Wi-Fi Kit	External Room Sensor			
AR-EH03E (Included as standard)	MWR-SH11N	MWR-WG00JN	MIM-H04EN	MRW-TA			

Performances are based on the following design condition

⁻ Nominal Cooling Capacity: Indoor temperature 27°C DB, 19°C WB, Outdoor temperature 35°C DB

⁻ UK Cooling Capacity: Indoortemperature 23°C DB,16°C WB, Outdoortemperature 30°C DB

² For units with capacity up to 12kW: Efficiencies as shown are according to EU No 206/2012 (LOT10) Ecodesign requirements for air conditioners.
For units with capacity up to 12kW: Energy labels as shown are according to EU No 626/2011 (LOT10) label classification 2019, on a scale from D to A+++.
For units with capacity greater than 12kW: Efficiencies as shown are according to EU No 2016/2281 (LOT21) Ecodesign requirements for heat pumps/air conditioners.