

SAMSUNG
Climate Solutions

VRF



WindFree™ 4way Mini Cassette

WindFree™ 4way Mini Cassette

- WindFree™ Cooling mode.
- Four-way air supply via independently adjustable blades.
- Built-in condensation drain pump and humidity sensor.
- Direct drive fan powered by a BLDC motor.

- Can be controlled by Smartphone via Wi-Fi Kit.
- Motion Detect Sensor (Optional).
- Predisposition of the air inlet to let fresh air in.

Specifications



Model			AM015NNNDEH/EU	AM022NNNDEH/EU	AM028NNNDEH/EU	AM036NNNDEH/EU
Electrical						
Power Supply	Ø, #, V, Hz		1Ø, 2, 220–240 V, 50 Hz	1Ø, 2, 220–240 V, 50 Hz	1Ø, 2, 220–240 V, 50 Hz	1Ø, 2, 220–240 V, 50 Hz
MCA	A		0.23	0.23	0.23	0.25
MFA	A		15	15	15	15
Interconnecting Communication Cable	mm ²		Screened 0.75-1.5mm ² , 2 Core, F1 F2 Connection			
Performance¹						
Nominal Cooling Capacity	Total Cooling (Sensible Cooling)	kW	1.5 (1.0)	2.2 (1.5)	2.8 (2.0)	3.6 (2.5)
UK Cooling Capacity	Total Cooling (Sensible Cooling)	kW	1.2 (1.0)	1.8 (1.4)	2.3 (1.8)	2.9 (2.2)
Nominal Heating Capacity		kW	1.70	2.50	3.20	4.00
Fan						
Type		-	Turbo Fan	Turbo Fan	Turbo Fan	Turbo Fan
Number of Fans		ea	1	1	1	1
Fan Motor	Model	-	BLDC Motor	BLDC Motor	BLDC Motor	BLDC Motor
	Output x n	W	65 x 1	65 x 1	65 x 1	65 x 1
Airflow Rate	H/M/L	m ³ /min	8.5 / 7.2 / 6.5	9.0 / 7.7 / 6.5	10.0 / 8.5 / 7.5	10.5 / 9.0 / 7.5
		l/s	142 / 120 / 108	150 / 128 / 108	167 / 142 / 125	175 / 150 / 125
Piping Connections						
Liquid Pipe	ø, mm (inch)		6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
Gas Pipe	ø, mm (inch)		12.70 (1/2)	12.70 (1/2)	12.70 (1/2)	12.70 (1/2)
Drain Pipe	ø, mm		VP25 (OD 32,ID 25)	VP25 (OD 32,ID 25)	VP25 (OD 32,ID 25)	VP25 (OD 32,ID 25)
Refrigerant						
Type			R410A (Fluorinated greenhouse gas, GWP=2088)			
Control Method			EEV included	EEV included	EEV included	EEV included
Sound						
Sound Pressure Level	H/M/L	dB(A)	30 / 28 / 23	32 / 29 / 25	33 / 30 / 26	34 / 30 / 26
Sound Power Level	Cooling	dB(A)	46	47	50	51
Dimensions						
Net Weight		kg	11.7	12	12	12
Net Dimensions	W x H x D	mm	575 x 250 x 575	575 x 250 x 575	575 x 250 x 575	575 x 250 x 575
Drain Pump						
Internal Model		-	Included	Included	Included	Included
External Model		-				
Max Lifting Height / Displacement		mm / litres/h	750 / 24	750 / 24	750 / 24	750 / 24
Default Panel						
Model Code		-	PC4SUFMAN	PC4SUFMAN	PC4SUFMAN	PC4SUFMAN
Net Weight		kg	2.7	2.7	2.7	2.7
Net Dimensions	W x H x D	mm	620 x 57 x 620	620 x 57 x 620	620 x 57 x 620	620 x 57 x 620
Colour		-	White	White	White	White

¹ Performances are based on the following design conditions:

- Nominal Cooling Capacity: Indoor temperature 27°C DB, 19°C WB, Outdoor temperature 35°C DB
- Nominal Heating Capacity: Indoor temperature 20°C DB, Outdoor temperature 7°C DB, 6°C WB
- UK Cooling Capacity: Indoor temperature 23°C DB, 16°C WB, Outdoor temperature 30°C DB

Accessories

Wireless Remote Controller	Touch Wired Controller	Premium Wired Controller
AR-EH03E	MWR-SH11N	MWR-WG00JN
Wi-Fi Kit	External Room Sensor	Motion Detect Sensor
MIM-H04EN	MRW-TA	MCR-SMD

Specifications



Model			AM045NNNDEH/EU	AM056NNNDEH/EU	AM060NNNDEH/EU
Electrical					
Power Supply		Ø, #, V, Hz	1Ø, 2, 220–240 V, 50 Hz	1Ø, 2, 220–240 V, 50 Hz	1Ø, 2, 220–240 V, 50 Hz
MCA		A	0.29	0.35	0.39
MFA		A	15	15	15
Interconnecting Communication Cable		mm ²	Screened 0.75-1.5mm ² , 2 Core, F1 F2 Connection		
Performance¹					
Nominal Cooling Capacity	Total Cooling (Sensible Cooling)	kW	4.5 (3.1)	5.6 (4.2)	6.0 (4.5)
UK Cooling Capacity	Total Cooling (Sensible Cooling)	kW	3.7 (2.8)	4.6 (3.8)	4.9 (4.0)
Nominal Heating Capacity		kW	5.00	6.30	6.80
Fan					
Type		-	Turbo Fan	Turbo Fan	Turbo Fan
Number of Fans		ea	1	1	1
Fan Motor	Model	-	BLDC Motor	BLDC Motor	BLDC Motor
	Output x n	W	65 x 1	65 x 1	65 x 1
Airflow Rate	H/M/L	m ³ /min	11.5 / 10.2 / 9.0	13.0 / 11.0 / 9.5	13.5 / 12.0 / 10.2
		l/s	192 / 170 / 150	217 / 183 / 158	225 / 200 / 170
Piping Connections					
Liquid Pipe		ø, mm (inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
Gas Pipe		ø, mm (inch)	12.70 (1/2)	12.70 (1/2)	12.70 (1/2)
Drain Pipe		ø, mm	VP25 (OD 32, ID 25)	VP25 (OD 32, ID 25)	VP25 (OD 32, ID 25)
Refrigerant					
Type			R410A (Fluorinated greenhouse gas, GWP=2088)		
Control Method			EEV included	EEV included	EEV included
Sound					
Sound Pressure Level	H/M/L	dB(A)	36 / 34 / 32	39 / 36 / 33	40 / 38 / 35
Sound Power Level	Cooling	dB(A)	53	56	57
Dimensions					
Net Weight		kg	12	12	12
Net Dimensions	W x H x D	mm	575 x 250 x 575	575 x 250 x 575	575 x 250 x 575
Drain Pump					
Internal Model		-	Included	Included	Included
External Model		-			
Max Lifting Height / Displacement		mm / litres/h	750 / 24	750 / 24	750 / 24
Default Panel					
Model Code		-	PC4SUFMAN	PC4SUFMAN	PC4SUFMAN
Net Weight		kg	2.7	2.7	2.7
Net Dimensions	W x H x D	mm	620 x 57 x 620	620 x 57 x 620	620 x 57 x 620
Colour		-	White	White	White

¹ Performances are based on the following design conditions:

- Nominal Cooling Capacity: Indoor temperature 27°C DB, 19°C WB, Outdoor temperature 35°C DB
- Nominal Heating Capacity: Indoor temperature 20°C DB, Outdoor temperature 7°C DB, 6°C WB
- UK Cooling Capacity: Indoor temperature 23°C DB, 16°C WB, Outdoor temperature 30°C DB